

STANDARD VERSION

Straight, rectangular seat shell, shaped to fit the body, with concealed screws. Made of multiplex, consisting of beech plywood, veneered crosswise. Standard in beech multiplex natural, environmentally friendly lacquered with water-based lacquer, edges softly rounded.

C-shape frame, round tube: 22/2.5 mm, standard version epoxy coated. With 3-component floor protector A2S FLOORSAFE®. Including plate and edge protectors to rest on the table top.

OPTIONS

- Shell with CPL coating
- Handle hole
- Seat upholstery price group 1 (size 6)Backrest upholstery price group 1
- (size 6)
- Seat upholstery price group 2 (size 6)
- Backrest upholstery price group 2 (size 6)
- Seat upholstery price group 3 (size 6)Backrest upholstery price group 3 (size 6)
- Seat upholstery price group 4 (size 6)
- Backrest upholstery price group 4 (size 6)
- FLOORSAFE® felt floor protectors
- Chair frame chrome platedCross brace (size 5-7)Series connection

STANDARD

DIN EN 1729-1, DIN EN 1729-2

FEMB level:2017 (Level 3)

SIZES

SIZE	6
CHAIR WIDTH	52 cm
CHAIR HEIGHT	91 cm
SEAT HEIGHT	46 cm
CHAIR DEPTH	53 cm
STACKABILITY	5 pcs.
WEIGHT	8 kg

LOAD CAPACITY

125 kg

BENEFITS/SPECIALS



Optionally with rectangular grip hole (not with backrest upholstery)



Optionally with seat and backrest upholstery



Seat shell optionally coated with scratch-resistant multiplex finish



Optionally with row connection from size 5



Seat shell environmentally friendly lacquered with water-based varnish



Body contoured seat shell



Robust C-shape frame with A2S FLOORSAFE® floor protectors



Stackable up to 5 chairs (without upholstery)



Plate and edge protectors protect the table when it is upended

FABRIC PROPERTIES

INTENSIVE Price group 1

100% polyester | flame retardant according to EN 1021 1&2 | 250 g/m2 +/-5% | 100,000 Martindale tours | linting 5 | \ddot{O} KO-Tex 100

SKANDIA Price group 1

100% polyester | flame retardant according to EN 1021 1 | 245 g/m2 +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex 100

FLEECE Price group 1

 $100\% \ polyester \ | \ flame \ retardant \ BS \ 5852: Part 1:1979 \ (cigarette) \ | \ 402 \ g/m2 \ | \ 100,000 \ Martindale \ tours \ | \ linting \ 4 \ | \ \ddot{O}KO-Tex \ 100$

TAFF B1 Price group 2

100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 260 g/m2 +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-Tex 100

WOOL Price group 3

100% wool | flame retardant according to EN 1021 1&2 | 460 g/m2 +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances

PROTEX Price group 3

surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 685 g/m2 | 300,000 Martindale tours | no linting | wipeable with soap and water, water repellent, antibacterial, anti-static, stain resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants

ARTIFICIAL LEATHER Price group 3

surface 100% polyurethane/ fabric 65% polyester, 35% cotton | flame retardant according to EN 1021-1 | 435 g/m2 +/-10% | 100,000 Martindale tours | no linting | tested for harmful substances

ARTIFICIAL LEATHER B1 Price group 4

85% PVC compound, 15% cotton knit | flame retardant according to EN 1021 1&2, DIN 4102 B1 | weight 780+/-50 g/m2 | 75,000 Martindale tours | no linting | tested for harmful substances | resistant to blood and urine, resistant to disinfectants