

FLEX 4-LEG CHAIR MODEL 7874



STANDARD VERSION

Plastic shell ergonomically shaped. Material made of polypropylene, recyclable, manufactured in double-wall blown process. Thus soft sitting due to air cushioning effect, with integrated ventilation channels and groove to relieve the spine. Grip hole in the lumbar region and recessed grips on the upper edge of the backrest and underside of the chair.

4-leg frame, round tube: 22/2.5 mm, standard version epoxy coated. With articulated floor protector.

OPTIONS

- Felt joint floor protectors
- Teflon floor protector
- Chair frame chrome plated
- Fully upholstered FLEX (size 5-7)
- Book tray (size 5-7)

STANDARD

FEMB level:2017 (Level 3)

DIN EN 1729-1, DIN EN 1729-2, DIN EN 16139

LOAD CAPACITY

125 kg

SIZES

SIZE	2	3	4	5	6	7
CHAIR WIDTH	43 cm	44 cm	45 cm	52 cm	54 cm	53 cm
CHAIR HEIGHT	62 cm	66 cm	69 cm	79 cm	82 cm	87 cm
SEAT HEIGHT	31 cm	35 cm	38 cm	43 cm	46 cm	51 cm
CHAIR DEPTH	35 cm	36 cm	37 cm	55 cm	54 cm	57 cm
STACKABILITY	3 pcs.	3 pcs.	3 pcs.	3 pcs.	3 pcs.	3 pcs.
WEIGHT	3 kg	3 kg	4 kg	5 kg	5 kg	6 kg

Our range of materials and colors can be found in the A2S material overview.



A2S-Furnishing Systems Ltd.
ASS-Einrichtungssysteme GmbH
info@a2s.com
WWW.A2S.COM

FLEX 4-LEG CHAIR MODEL 7874



BENEFITS/SPECIALS



Easy to carry due to low weight




Optionally with book tray from size 5



Optional seat shell fully upholstered from size 5 onwards



Seat shell with integrated ventilation channel



Robust 4-leg frame



Stackable up to 3 chairs
(without upholstery)

FABRIC PROPERTIES

FLEX upholstery

Flame retardant according to DIN 4102 B1 | 250 g/m² +/-5% | 40,000 Martindale tours | Linting 4 | ÖKO-Tex 100