



STANDARD VERSION

Straight, rectangular seat shell, shaped to fit the body, with concealed screws. Made of multiplex, consisting of beech plywood, veneered crosswise. Standard in beech multiplex natural, environmentally friendly lacquered with water-based lacquer, edges softly rounded.
Plastic 5-star base in black, with infinitely variable gas lift height adjustment. Round tubular column: 50 mm. With plastic feet.

OPTIONS

- Shell with CPL coating
 - Handle hole
 - Seat upholstery price group 1 (size 6)
 - Backrest upholstery price group 1 (size 6)
 - Seat upholstery price group 2 (size 6)
- Backrest upholstery price group 2 (size 6)
 - Seat upholstery price group 3 (size 6)
 - Backrest upholstery price group 3 (size 6)
 - Seat upholstery price group 4 (size 6)
 - Backrest upholstery price group 4 (size 6)
- Partial foot ring
 - 3D rocking mechanism
 - Felt floor protectors
 - Load-dependent braking casters (SH +3 cm)

STANDARD

DIN EN 1729-1, DIN EN 1729-2, DIN EN 16139
GS-zertifiziert gem. DIN EN 1729-1, DIN EN 1729-2

LOAD CAPACITY

125 kg

SIZES

SIZE	5-7
CHAIR WIDTH	62 cm
CHAIR HEIGHT	84-99 cm
SEAT HEIGHT	39-53 cm
CHAIR DEPTH	62 cm
STACKABILITY	-
WEIGHT	7 kg

BENEFITS/SPECIALS



Optionally with rectangular grip hole (not with backrest upholstery)



Optionally with seat and backrest upholstery



Seat shell optionally coated with scratch-resistant multiplex finish



Height adjustment by safety gas spring



Optionally with load-dependent braked casters



Optionally with partial foot ring



Seat shell environmentally friendly lacquered with water-based varnish



Body contoured seat shell



Extremely robust black plastic base

FABRIC PROPERTIES

INTENSIVE Price group 1

100% polyester | flame retardant according to EN 1021 1&2 | 250 g/m² +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-Tex 100

SKANDIA Price group 1

100% polyester | flame retardant according to EN 1021 1 | 245 g/m² +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex 100

FLEECE Price group 1

100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 402 g/m² | 100,000 Martindale tours | linting 4 | ÖKO-Tex 100

TAFF B1 Price group 2

100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 260 g/m² +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-Tex 100

WOOL Price group 3

100% wool | flame retardant according to EN 1021 1&2 | 460 g/m² +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances

PROTEX Price group 3

surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 685 g/m² | 300,000 Martindale tours | no linting | wipeable with soap and water, water repellent, antibacterial, anti-static, stain resistant, resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants

ARTIFICIAL LEATHER Price group 3

surface 100% polyurethane/ fabric 65% polyester, 35% cotton | flame retardant according to EN 1021-1 | 435 g/m² +/-10% | 100,000 Martindale tours | no linting | tested for harmful substances

ARTIFICIAL LEATHER B1 Price group 4

85% PVC compound, 15% cotton knit | flame retardant according to EN 1021 1&2, DIN 4102 B1 | weight 780 +/-50 g/m² | 75,000 Martindale tours | no linting | tested for harmful substances | resistant to blood and urine, resistant to disinfectants