



STANDARD VERSION

Straight, rectangular seat shell, shaped to fit the body, with concealed fastening. Seat support made of beech plywood, fully upholstered.

Cantilever frame, firmly welded. Round tube: 22/2.5 mm. Frame chrome-plated, with plastic floor protectors.

OPTIONS

- Full upholstery price group 2
- Full upholstery price group 3 (imitation leather)
- Full upholstery price group (PROTEX)
- Full upholstery price group 3 (WOOL)
- Full upholstery price group 4 (artificial leather B1)
- Felt floor protectors

LOAD CAPACITY

125 kg

SIZES

SIZE	6
CHAIR WIDTH	44 cm
CHAIR HEIGHT	89 cm
SEAT HEIGHT	46 cm
CHAIR DEPTH	55 cm
STACKABILITY	-
WEIGHT	8 kg

BENEFITS/SPECIALS



Body contoured seat shell with full upholstery



Extremely robust cantilever frame

FABRIC PROPERTIES

INTENSIVE Price group 1

100% polyester | flame retardant according to EN 1021 1&2 | 250 g/m² +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-Tex 100

SKANDIA Price group 1

100% polyester | flame retardant according to EN 1021 1 | 245 g/m² +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex 100

FLEECE Price group 1

100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 402 g/m² | 100,000 Martindale tours | linting 4 | ÖKO-Tex 100

TAFF B1 Price group 2

100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 260 g/m2 +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-Tex 100

WOOL Price group 3

100% wool | flame retardant according to EN 1021 1&2 | 460 g/m2 +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances

PROTEX Price group 3

surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 685 g/m2 | 300,000 Martindale tours | no linting | wipeable with soap and water, water repellent, antibacterial, anti-static, stain resistant, resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants

ARTIFICIAL LEATHER Price group 3

surface 100% polyurethane/ fabric 65% polyester, 35% cotton | flame retardant according to EN 1021-1 | 435 g/m2 +/-10% | 100,000 Martindale tours | no linting | tested for harmful substances

ARTIFICIAL LEATHER B1 Price group 4

85% PVC compound, 15% cotton knit | flame retardant according to EN 1021 1&2, DIN 4102 B1 | weight 780 +/-50 g/m2 | 75,000 Martindale tours | no linting | tested for harmful substances | resistant to blood and urine, resistant to disinfectants