

OFFICE DESK, ELECTRICALLY HEIGHT ADJUSTABLE (120X90 CM)

MODEL 5580.129



STANDARD VERSION

Tabletop, 3-layer chipboard (E1), melamine coated, highly abrasion-resistant, with 3 mm plastic edge, thickness: 25 mm.

Note: Table height specifications refer to a tabletop thickness of 25 mm.

Maximum load capacity of table top: 100 kg.

Center column frame height adjustable by electric motor, rectangular steel tube. Lifting speed: 38 mm/s (without load). Lifting load per column: 800 N. Foldable metal cable tray under the table top including 6-fold Schuko socket with 3 m cable supply. Powder coated frame. Steel runners with plastic floor protectors with level compensation.

Hand switch for height adjustment optionally mounted on the left or right.

Table top shape: rectangular

OPTIONS

- Table top finishes price group 2
- Table top HPL glued
- Cable opening, Ø 80 mm
- Cable opening, Ø 90 mm
- CPU holder
- Cable slack
- Table frame black
- Table frame white
- Manual switch with memory function
- Brush on trailing edge

STANDARD

GS-zertifiziert gem. EK5/AK3 13-01

SIZES

TABLE WIDTH	120 cm
TABLE HEIGHT	62-127 cm
TABLE DEPTH	90 cm
STACKABILITY	-
NUMBER OF SEATS	1
WEIGHT	44 kg

Our range of materials and colors can be found in the A2S material overview.



A2S-Furnishing Systems Ltd.
ASS-Einrichtungssysteme GmbH
info@a2s.com
WWW.A2S.COM

OFFICE DESK, ELECTRICALLY HEIGHT ADJUSTABLE (120X90 CM)

MODEL 5580.129




BENEFITS/SPECIALS



Melamine coated table top with robust plastic edge



Manual switch with up and down function or optional memory function



Concealed cable management through foldable cable tray



Floor protectors with level compensation for easy leveling of uneven floors



Collision protection minimizes the risk of damage when moving up and down



Matching accessories: Front cover model 2050.122



Infinitely and quietly height adjustable in the range 62-127 cm