

# 4-LEGGED ROW STACKING TABLE, METAL WELDED (130X55 CM)

MODEL 1026.135



## STANDARD VERSION

Tabletop, 3-layer chipboard (E1), melamine coated, highly abrasion-resistant, with 3 mm plastic edge, thickness: 25 mm.

**Note:** Table height specifications refer to a tabletop thickness of 25 mm.

4-leg base frame, side parts round tube: 40/2 mm, frame square tube welded and rounded: 40/20/2 mm. Frame epoxy coated, with plastic floor protector with level compensation.

Rear table legs lengthwise, projecting laterally, thus stackable and can be placed next to each other without joints.

Table top shape: rectangular

## OPTIONS

- Table top finishes price group 2
- Tabletop with ASSODUR® edge
- Table top HPL glued
- Felt floor protectors
- Teflon floor protector
- 2 rollers lengthwise
- Table frame chrome plated
- Chair suspension PAGHOLZ® sled-base chair
- 1 pair of rails for Tidy Box
- Folder hook

## STANDARD

GS-zertifiziert gem. DIN EN 1729-1, DIN EN 1729-2, DIN EN 15372

## SIZES

SIZE	3	4	5	6	7	72 cm	75 cm
TABLE WIDTH	130 cm	130 cm	130 cm	130 cm	130 cm	130 cm	130 cm
TABLE HEIGHT	58 cm	64 cm	70 cm	76 cm	82 cm	72 cm	75 cm
TABLE DEPTH	55 cm	55 cm	55 cm	55 cm	55 cm	55 cm	55 cm
PLAN DIMENSION	140x55 cm	140x55 cm	140x55 cm	140x55 cm	140x55 cm	140x55 cm	140x55 cm
STACKABILITY	4 pcs.	4 pcs.	4 pcs.	4 pcs.	4 pcs.	4 pcs.	4 pcs.
NUMBER OF SEATS	2	2	2	2	2	2	2
WEIGHT	22 kg	22 kg	23 kg	23 kg	24 kg	23 kg	24 kg

Our range of materials and colors can be found in the A2S material overview.



A2S-Furnishing Systems Ltd.  
ASS-Einrichtungssysteme GmbH  
info@a2s.com  
WWW.A2S.COM

# 4-LEGGED ROW STACKING TABLE, METAL WELDED

(130X55 CM)

MODEL 1026.135



## BENEFITS/SPECIALS



Melamine coated table top with robust plastic edge



Optional melamine coated table top with ASSODUR® edge



Floor saver with level compensation compensates for uneven floors



Optional frame mobile by means of 2 rollers



Optionally with one folder hook per seat



Stackable up to 4 tables due to special frame design



Table tops can be placed together without joints