

4-LEG TABLE, METAL WELDED (120X60 CM) MODEL 1001.135



STANDARD VERSION

Tabletop, 3-layer chipboard (E1), melamine coated, highly abrasion-resistant, with 3 mm plastic edge, thickness: 25 mm.

Note: Table height specifications refer to a tabletop thickness of 25 mm.

4-leg base frame, side parts round tube: 40/2 mm, frame square tube welded and rounded: 40/20/2 mm. Frame epoxy coated, with plastic floor protector with level compensation.

Table top shape: rectangular

OPTIONS

- Table top finishes price group 2
- Tabletop with ASSODUR® edge
- Table top HPL glued
- Table top compact board 12 mm
- Table top with 40 mm corner radius
- Cable opening, Ø 80 mm
- Cable opening, Ø 90 mm
- Mesh cable duct
- Felt floor protectors
- Teflon floor protector
- Fixed castor
- Table frame chrome plated
- Height adjustment 3-7
- CPU holder
- Insert plate for CPU holder
- Cable slack
- Cable clamp Ø 38-40 mm
- 6-fold gounded socket

STANDARD

GS-zertifiziert gem. DIN EN 1729-1, DIN EN 1729-2, DIN EN 15372

FEMB level:2017 (Level 3)

SIZES

| SIZE | 3 | 4 | 5 | 6 | 7 | 72 cm | 75 cm |
|-----------------|--------|--------|--------|--------|--------|--------|--------|
| TABLE WIDTH | 130 cm | 130 cm | 130 cm | 130 cm | 130 cm | 130 cm | 130 cm |
| TABLE HEIGHT | 58 cm | 64 cm | 70 cm | 76 cm | 82 cm | 72 cm | 75 cm |
| TABLE DEPTH | 50 cm | 50 cm | 50 cm | 50 cm | 50 cm | 50 cm | 50 cm |
| STACKABILITY | - | - | - | - | - | - | - |
| NUMBER OF SEATS | 2 | 2 | 2 | 2 | 2 | 2 | 2 |
| WEIGHT | 21 kg | 21 kg | 22 kg | 22 kg | 23 kg | 22 kg | 22 kg |

Our range of materials and colors can be found in the A2S material overview.



A2S-Furnishing Systems Ltd.
ASS-Einrichtungssysteme GmbH
info@a2s.com
WWW.A2S.COM


4-LEG TABLE, METAL WELDED (120X60 CM) MODEL 1001.135



BENEFITS/SPECIALS



Melamine coated table top with robust plastic edge



Optional compact board as table top




Optional table top with 40 mm corner radius



Floor saver with level compensation compensates for uneven floors



Optional frame mobile by means of 2 fixed castors



Optional melamine coated table top with ASSODUR® edge